

GM268

20°/60°/85° GLOSS METER



- ◆ To test the gloss of painting, printing ink, surfaces of future metal, granite, ceramic, plastic, paper, etc.
- ◆ Conforms to ISO 2813, ASTM D 2457, ASTM D 523
- ◆ Large display screen



SPECIFICATION

Incidence angle	20°	60°	85°
Measuring range	0~2000GU	0~1000GU	0~160GU
Resolution	0.1GU (range<119.9GU)		
Accuracy	±1.5GU (range<100GU)		
	±1.5% (range>100GU)		
Repeatability	±0.1GU (range<10GU)		
	±0.2GU (range: 10~100GU)		
	±0.2% (range>100GU)		
Measuring speed	1s		
Measuring area	10×10mm	15×9mm	36×5mm
Power supply	Rechargeable battery		
Dimension	160×75×90mm		
Weight	350g		

INCLUDED ACCESSORIES

Main unit	1pc
Calibration block	1pc
USB cable and software	1pc

GM60

60° GLOSS METER



- ◆ Basic type
- ◆ To test the gloss of painting, printing ink, surfaces of future metal, granite, ceramic, plastic, paper, etc.
- ◆ Conforms to ISO 2813, ASTM D 2457, ASTM D 523



SPECIFICATION

Incidence angle	60°
Measuring range	0~200GU
Measuring area	9x15mm
Resolution	1GU
Repeatability	±1GU (0-100GU), ±1%GU (100-200GU)
Measuring speed	0.5S
Power supply	AA battery
Dimension	160x52x84mm
Weight	300g

INCLUDED ACCESSORIES

Main unit	1pc
Calibration block	1pc
AA battery	1pc

PORTABLE

ACECAD

