




TMCx-HD Sensor

Air/Water/Soil Temperature Sensor

The TMC temperature probe can be used in air, soil & water work with the UX120-006M, ZW Series or U Series of data loggers. Temperature probes are available in lengths of 0.3 m (1 ft), 1.8 m (6 ft), 6.1 m, (20 ft) & 15.2 m (50 ft).

Supported Measurements:

Temperature and Water Temperature



Key Advantages:

- Plug directly into the external input jacks of U12, UX120, or ZW Family loggers to expand the range of measurement options and applications

TMCx-HD Sensor Specifications

Measurement range: -40° to 50°C (-40° to 122°F) in water; -40° to 100°C (-40° to 212°F) in air

Accuracy:

w/U12: ±0.25°C from 0° to 50°C (±0.45°F from 32° to 122°F), insert probe 2.3 cm (0.9 inches) minimum;

w/ZW: ±0.21°C from 0° to 50°C (±0.38°F from 32° to 122°F), insert probe 2.3 cm (0.9 inches) minimum;

w/UX120-006M, MX1104, and MX1105: ±0.15°C from 0° to 70°C (±0.27°F from 32° to 158°F), insert probe 2.3 cm (0.9 inches) minimum;

Resolution:

w/U12: 0.03° at 20°C (0.05° at 68°F);

w/ZW: 0.02°C at 25°C (0.04°F at 77°F);

w/UX120-006M, MX1104, and MX1105: 0.002° at 25°C (0.003° at 77°F);

Drift: <0.1°C (<0.2°F) per year

Response time in air: 2 min. typical to 90% in air moving 1 m/sec (2.2 mph)

Response time in stirred water: 30 sec. typical to 90%.

Operating range: Sensor tip and cable immersion in fresh water up to +50°C (122°F) for 1 year

Housing: Copper-plated sensor tip

Dimensions: 5.1 x 33 mm (0.2 x 1.3 inches)

Weight: 34 g (1.1 oz)

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

▶ Email sales@onsetcomp.com

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-800-564-4377

▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

▶ Contact Product Support www.onsetcomp.com/support/contact

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation

470 MacArthur Boulevard

Bourne, MA 02532